



Features

- Designed for residential and light commercial applications where duty is not severe.
- Listed per UL Standard 90, Enclosed and Dead Front Switches.
- UL Service Entrance rated when installed in accordance with the National Electrical Code.
- Meets NEMA Enclosed Switch Standard KS1-1990 for Type.
- General Duty.
- Pad-lockable in off position.
- Underground and overhead Exit/Entry provisions standard from factory.
- Hinge cover screw fastened door construction.
- Roof Knockout sealable cover plates available and sold separately.
- Active safety latch keeps cover closed when switch is in on position.
- Neutral to ground bonding kit included standard.
- Line side top configuration standard, Line bottom configuration available by request.
- 60°C and 75°C conductor rating.
- Disconnect switches are fused.

Product Selection

Part Number	Amperage (A)	Voltage (V)	Phase/Wires	Type	H x W x D (Inches)	Fuse Type
NAV-SS 200-3-F	200	250 MAX	3PH/4W	INDOOR	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 200-3-F-R	200	250 MAX	3PH/4W	OUTDOOR	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 200-2-F	200	250 MAX	1PH/3W	INDOOR	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 200-2-F-R	200	250 MAX	1PH/3W	OUTDOOR	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 400-3-F	400	250 MAX	3PH/4W	INDOOR	49.5 x 22 x 10-1/2	(H) or (K)
NAV-SS 400-3-F-R	400	250 MAX	3PH/4W	OUTDOOR	49.5 x 22 x 10-1/2	(H) or (K)
NAV-SS 400-2-F	400	250 MAX	1PH/3W	INDOOR	49.5 x 22 x 10-1/2	(H) or (K)
NAV-SS 400-2-F-R	400	250 MAX	1PH/3W	OUTDOOR	49.5 x 22 x 10-1/2	(H) or (K)