

BUS BARS - COPPER 98% CONDUCTIVITY

B

- 3. ENCLOSURE WILL DISPLAY MANUFACTURERS NAME
- ALL NUTS, BOLTS AND WASHERS MUST BE 1/2-13 ZINC COATED GRADE 5 STEEL
- 5. MAX WIRE SIZE LINE AND LOAD SIDE: (3) 600 MCM OR (6) 250 MCM LEADS (MINIMUM WIRE SIZE:#4)
- FRONT DOOR IS OUTFITTED WITH SEALABLE SCREWS & PADLOCKABLE PROVISIONS
- DESIGNED FOR EITHER LINE TOP/LOAD BOTTOM CABLE ENTRY OR LOAD TOP/LINE BOTTOM CABLE ENTRY

NAME DATE DRAWN BY N.BOSETTI 9/6/2024 APPROVED BY

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Nav-Tech Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Nav-Tech Inc. IS PROHIBITED.



155 MARCUS BLVD HAUPPAUGE, NEW YORK 11788 PH: (718) 257-2111 FAX: (718) 257-2626

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE NOMINAL UNLESS EXPLICITLY STATED OTHERWISE

MAT'L: 12 GA GALV FINISH. POWDER COAT ANSI 61 GY **WEIGHT:** N/A

UNLESS OTHERWISE SPECIFIED

1. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES .015 X 45° OR .015R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING

MACHINED SURFACES EXCEPT AS NOTED

DRAWING TITLE:

298CT N1 SPEC SHEET

PART #: NAV-298CT-1200

DESCRIPTION: NEMA 1 298 CT CABINET 1200 AMP 600 VAC MAX SPECIFIED TO CON ED MES 298

DO NOT SCALE **DRAWING**