

B


B

PART NUMBER	AMPS	MAX VOLTS	FEED	SWITCH	LUGS	INSTALLATION TYPE	CABINET SIZE INDOOR HxWxD	CABINET SIZE OUTDOOR* HxWxD
400BPS-T	400A	600V	TOP	J365WOL	1 SET 600MCM	3-PHASE 3-WIRE**	58 X 22 X 11.5	58 X 26 X 14.5
400BPS-B		600V	BOTTOM	JB365WOL				
600BPS-T	600A	600V	TOP	J366WOL	2 SETS 600MCM			
600BPS-B		600V	BOTTOM	JB366WOL				
800BPS-T	800A	600V	TOP	L367-A				
800BPS-B		600V	BOTTOM	LB367-A				
1200BPS-T	1200A	600V	TOP	VL468N	3 SETS 600MCM	3-PHASE 4-WIRE	66 X 36 X 18	66 X 40 X 21
1200BPS-B		600V	BOTTOM	VLB468N				
1600BPS-T	1600A	600V	TOP	VL469N	4 SETS 600MCM			
1600BPS-B		600V	BOTTOM	VLB469N				
2000BPS-T	2000A	600V	TOP	VL4610N	5 SETS 600MCM			
2000BPS-B		600V	BOTTOM	VLB4610N				
2500BPS-T	2500A	600V	TOP	VL4611N	6 SETS 600MCM			
2500BPS-B		480V	BOTTOM	VLB4611N				
3000BPS-T	3000A	600V	TOP	VL4612N	8 SETS 600MCM			
3000BPS-B		480V	BOTTOM	VLB4412N				
4000BPS-T	4000A	600V	TOP	SL4613N	10 SETS 600MCM		75 X 42 X 18	75 X 42 X 21
4000BPS-B		480V	BOTTOM	SLB4413N				

* FOR OUTDOOR CABINET, ADD SUFFIX "-N3R" TO PART NUMBER
 ** FOR 400A-800A, 3-WIRE IS STANDARD. 4-WIRE IS AVAILABLE BY REQUEST
 *** ARC FLASH REDUCTION AND GROUND FAULT RELAY AVAILABLE BY REQUEST

A

A

DRAWN BY	NAME N. BOSETTI	DATE 2/11/2025		MAT'L:	12 GAUGE GALV STEEL	DRAWING TITLE:	TABLE FOR ENCLOSED BPS					
REVIEWED BY				FINISH:	GRAY POWDER COAT ANSI 61	PART #:	XXXXBPS-X					
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAV-TECH INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAV-TECH INC. IS PROHIBITED.				WEIGHT:		DO NOT SCALE DRAWING						
155 MARCUS BLVD HAUPPAUGE, NEW YORK 11788 PH: (718) 257-2111 FAX: (718) 257-2626			ALL DIMENSIONS ARE NOMINAL UNLESS EXPLICITLY STATED OTHERWISE		SCALE:					1:20	SIZE	A