



PHASE SIDE VIEW NOTES:

- NEMA 3R CONSTRUCTION INCLUDES SHED ROOF , EXTERNAL MOUNTING TABS ON ALL FOUR CORNERS,GASKETED COVERS AND DOORS ALONG WITH SHED ROOF AND SKIRTED, GASKETED MIDDLE DOORS
- BUS BARS - COPPER 98% CONDUCTIVITY
- ENCLOSURE WILL DISPLAY MANUFACTURERS NAME
- ALL NUTS, BOLTS AND WASHERS MUST BE 1/2-13 ZINC COATED GRADE 5 STEEL
- MAX WIRE SIZE LINE AND LOAD SIDE: (3) 600 MCM OR (6) 250 MCM LEADS (MINIMUM WIRE SIZE:#4)
- FRONT DOOR IS OUTFITTED WITH SEALABLE SCREWS & PADLOCKABLE PROVISIONS
- DESIGNED FOR EITHER LINE TOP/LOAD BOTTOM CABLE ENTRY OR LOAD TOP/LINE BOTTOM CABLE ENTRY

| | NAME | DATE |
|--|-----------|----------|
| DRAWN BY | N.BOSETTI | 5/2/2024 |
| APPROVED BY | | |
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Nav-Tech Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Nav-Tech Inc. IS PROHIBITED. | | |



155 MARCUS BLVD
HAUPPAUGE, NEW YORK 11788
PH: (718) 257-2111 FAX: (718) 257-2626

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE NOMINAL UNLESS EXPLICITLY STATED OTHERWISE

| | |
|---|------------------------|
| MAT'L: | 12 GA GALV |
| FINISH: | POWDER COAT ANSI 61 GY |
| WEIGHT: | N/A |
| UNLESS OTHERWISE SPECIFIED: | |
| 1. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES .015 X 45° OR .015R | |
| 2. DIMENSIONAL LIMITS APPLY AFTER PLATING | |
| 3. $\frac{125}{\checkmark}$ MACHINED SURFACES EXCEPT AS NOTED | |

| | | | | |
|-----------------------------|---|---------------|---------------------|---------------|
| DRAWING TITLE: | 298CT N3R SPEC SHEET | | | |
| PART #: | NAV-298CT-1200-N3R | | | |
| DESCRIPTION: | NEMA 3R 298 CT CABINET 1200 AMP SPECIFIED TO CON ED MES 298 | | | |
| DO NOT SCALE DRAWING | SCALE 1:10 | SIZE A | SHEET 1 OF 1 | REV. 3 |

