



PHASE SIDE VIEW

OPEN FRONT VIEW

NEUTRAL SIDE VIEW

COVERED FRONT VIEW

COVERED SIDE VIEW

NOTES:

1. NEMA 1 CONSTRUCTION INCLUDES STITCH WELDED SCREW FASTENED ENCLOSURE
2. BUS BARS - COPPER 98% CONDUCTIVITY
3. ENCLOSURE WILL DISPLAY MANUFACTURERS NAME
4. ALL NUTS, BOLTS AND WASHERS MUST BE 1/2-13 ZINC COATED GRADE 5 STEEL
5. MAX WIRE SIZE LINE AND LOAD SIDE: (4) 600 MCM OR (8) 250 MCM LEADS (MINIMUM WIRE SIZE: #4)
6. FRONT DOOR IS OUTFITTED WITH SEALABLE SCREWS & PADLOCKABLE PROVISIONS
7. DESIGNED FOR EITHER LINE TOP/LOAD BOTTOM CABLE ENTRY OR LOAD TOP/LINE BOTTOM CABLE ENTRY

	NAME	DATE
DRAWN BY	N. BOSETTI	5/2/2024
APPROVED BY		

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Nav-Tech Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Nav-Tech Inc. IS PROHIBITED.



155 MARCUS BLVD
 HAUPPAUGE, NEW YORK 11788
 PH: (718) 257-2111 FAX: (718) 257-2626

UNLESS OTHERWISE SPECIFIED:
 ALL DIMENSIONS ARE NOMINAL UNLESS EXPLICITLY STATED OTHERWISE

MAT'L: 12 GA GALV
 FINISH: POWDER COAT ANSI 61 GY
 WEIGHT: N/A

UNLESS OTHERWISE SPECIFIED

1. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES .015 X 45° OR .015R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING
3. $\frac{125}{\checkmark}$ MACHINED SURFACES EXCEPT AS NOTED

DRAWING TITLE: 298CT N1 SPEC SHEET

PART #: NAV-298CT-1600

DESCRIPTION: NEMA 1 298 CT CABINET
 1600 AMP
 SPECIFIED TO CON ED MES 298

DO NOT SCALE DRAWING	SCALE 1:10	SIZE A	SHEET 1 OF 1	REV. 3
-----------------------------	------------	--------	--------------	--------

A

A

2

1