



PHASE SIDE VIEW NOTES:

1. NEMA 3R CONSTRUCTION INCLUDES SHED ROOF , EXTERNAL MOUNTING TABS ON ALL FOUR CORNERS,GASKETED COVERS AND DOORS ALONG WITH SHED ROOF AND SKIRTED, GASKETED MIDDLE DOORS
2. BUS BARS - COPPER 98% CONDUCTIVITY
3. ENCLOSURE WILL DISPLAY MANUFACTURERS NAME
4. ALL NUTS, BOLTS AND WASHERS MUST BE 1/2-13 ZINC COATED GRADE 5 STEEL
5. MAX WIRE SIZE LINE AND LOAD SIDE: (2)600 MCM OR (4) 250 MCM LEADS (MINIMUM WIRE SIZE:#4)
6. FRONT DOOR IS OUTFITTED WITH SEALABLE SCREWS & PADLOCKABLE PROVISIONS
7. DESIGNED FOR EITHER LINE TOP/LOAD BOTTOM CABLE ENTRY OR LOAD TOP/LINE BOTTOM CABLE ENTRY

| | NAME | DATE |
|-------------|-----------|----------|
| DRAWN BY | N.BOSETTI | 5/2/2024 |
| APPROVED BY | | |

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Nav-Tech Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Nav-Tech Inc. IS PROHIBITED.



155 MARCUS BLVD
 HAUPPAUGE, NEW YORK 11788
 PH: (718) 257-2111 FAX: (718) 257-2626

UNLESS OTHERWISE SPECIFIED:
 ALL DIMENSIONS ARE NOMINAL UNLESS EXPLICITLY STATED OTHERWISE

MAT'L: 12 GA GALV
FINISH: POWDER COAT ANSI 61 GY
WEIGHT: N/A

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES .015 X 45° OR .015R
 2. DIMENSIONAL LIMITS APPLY AFTER PLATING

3. 125/ MACHINED SURFACES EXCEPT AS NOTED

| | | | | |
|-----------------------------|--|---------------|---------------------|---------------|
| DRAWING TITLE: | 298CT N3R SPEC SHEET | | | |
| PART #: | NAV-298CT-800-N3R | | | |
| DESCRIPTION: | NEMA 3R 298 CT CABINET 800 AMP SPECIFIED TO CON ED MES 298 | | | |
| DO NOT SCALE DRAWING | SCALE 1:10 | SIZE A | SHEET 1 OF 1 | REV. 3 |

