

Duke Commercial Utility Service Package



Features (Cabinets)

- Box and cover N3R construction - galvanized sheet steel (16GA).
- Finish: Powdercoat gray enamel.
- Manufacturer name plate included.
- CT mounting backplates & hardware included.
- Embossed holes in rear for mounting cabinet.
- N-150 bonded grounding lug.
- *Cover type either hinge or liftoff.

Features (Meters)

- ANSI 61 powder coated galvanized steel, aluminum or stainless steel options.
- UL Listed.
- Ringless type meter opening.
- Duke utility specific test switch pole arrangements.
- Clear lexan or black fiberglass test switch covers available.
- Standard utility sealable options.
- 1 piece front cover.
- Duke utility specific wire harnesses.
- Arc barrier standard.

Product Selection

	Part Number	Enclosure Size (Inches H x W x D)	Amperage (A)	Installation Type	Installation Voltage (MAX Volts AC)	Max Conductors Per Phase	Material / Construction	*Cover Type
CT Cabinets	NAV-DE-CTR-6	34 x 32 x 12	600	1 or 3 - Phase 4-Wire	600	See Duke Energy regional service requirements	14GA Galv Steel NEMA 3R	Lift-Off Screw Cover w/ Sealing Latch
	NAV-DE-CTR-12	40 x 40 x 14	1200	1 or 3 - Phase 4-Wire	600	See Duke Energy regional service requirements	14GA Galv Steel NEMA 3R	Padlockable French Door w/ 3-Point Catch

	Part Number	Enclosure Size (Inches H x W x D)	Amperage (A)	Installation Type	Installation Voltage (MAX Volts AC)
Meters	NAV-DECM-MS10P-3	20 x 12.25 x 5	30	3-Phase 4-Wire	600
	NAV-DECM-MS10P-1	21 x 14.25 x 5	30	1-Phase 3-Wire	600