

FPL Commercial Utility Service Package



Features (Cabinets)

- Box and cover N3R construction - galvanized sheet steel (14GA).
- Finish: Powdercoat gray enamel.
- UL 414 listed.
- Manufacturer name plate included.
- 800A or 1200A, 600VAC MAX 3Ø 4W - rated for 50kA SCCR.
- Grade 5 hardware.
- Wire connection torque: 500 in-lb.
- CT landing bolt torque: 660 in-lb.

Features (Meters)

- ANSI 61 powder coated galvanized steel, aluminum or stainless steel options.
- UL Listed.
- Ringless type meter opening.
- FPLC utility specific test switch pole arrangements.
- Clear lexan or black fiberglass test switch covers available.
- Standard utility sealable options.
- 1 piece front cover.
- FPLC utility specific wire harnesses.
- Arc barrier standard.

Product Selection

| | Part Number | Enclosure Size (Inches H x W x D) | Installation Type | Installation Voltage (MAX Volts AC) | Max Conductors Per Phase | Material / Construction |
|-------------|--------------------|-----------------------------------|-------------------|-------------------------------------|--------------------------|-------------------------|
| CT Cabinets | NAV-FPL-CTR-12 | 34 x 32 x 12 | 3-Phase 4-Wire | 600 | 2 Sets 600MCM | 14GA Galv Steel NEMA 3R |
| | NAV-FPL-CTR-463015 | 46 x 30 x 15 | 3-Phase 4-Wire | 600 | 4 Sets 600MCM | 14GA Galv Steel NEMA 3R |
| | NAV-FPL-CTR-544215 | 54 x 42 x 15 | 3-Phase 4-Wire | 600 | 4 Sets 600MCM | 14GA Galv Steel NEMA 3R |
| | NAV-FPL-CTR-XL | 46 x 30 x 16 (MIN dimensions) | 3-Phase 4-Wire | 600 | As Required | 14GA Galv Steel NEMA 3R |

| | Part Number | Enclosure Size (Inches H x W x D) | Amperage (A) | Installation Type | Installation Voltage (MAX Volts AC) |
|--------|-----------------|-----------------------------------|--------------|-------------------|-------------------------------------|
| Meters | NAV-FPL-MS10P-3 | 20 x 12.25 x 5 | 30 | 3-Phase 4-Wire | 600 |
| | NAV-FPL-MS7P-1 | 21 x 14.25 x 5 | 30 | 1-Phase 3-Wire | 600 |