



## Features (Cabinets)

- Enclosure body and cover constructed of galvanized steel.
- ANSI 61 gray polyester powder paint finish inside and out.
- Double door configuration with 3-point latch and padlockable handle.
- Single door configuration screw fastened with padlockable handle.
- Grounding stud for equipment grounding.
- Nema 3R outdoor Shed roof Construction preventing rain water ingress.
- Gasketed front cover With provisions to hold doors open.
- Lift off hinges factory installed.
- No knockouts.
- Galvanized steel backplate factory installed.
- UL Listed.

## Features (Disconnects)

- 200A-4000A MAX 600V disconnects available.
- Listed per UL Standard 90, enclosed and dead front witches.
- UL Service Entrance rated when installed in accordance with the National Electrical Code.
- General or heavy duty.
- Pad-lockable in off position.
- Underground and overhead exit/entry provisions.
- Neutral to ground bonding kit included standard.
- Line side top configuration standard, line bottom configuration available by request.
- Disconnect switches are fused.

## Product Selection (Disconnects)

Part Number	Amperage (A)	Voltage (V)	Phase/Wires	Type	H x W x D (Inches)	Fuse Type
NAV-SS 200-3-F	200	250 MAX	3PH/4W	Indoor	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 200-3-F-R	200	250 MAX	3PH/4W	Outdoor	31-1/4 x 13 x 7	(H) or (K)
NAV-SS 400-3-F	400	250 MAX	3PH/4W	Indoor	49.5 x 22 x 10-1/2	(H) or (K)
NAV-SS 400-3-F-R	400	250 MAX	3PH/4W	Outdoor	49.5 x 22 x 10-1/2	(H) or (K)
(Amps) BPS-T	400-4000	600 MAX	3PH/4W	Indoor	Variable	(J) or (L)
(Amps) BPS-B	400-4000	600 MAX	3PH/4W	Indoor	Variable	(J) or (L)
(Amps) BPS-T-3R	400-4000	600 MAX	3PH/4W	Outdoor	Variable	(J) or (L)
(Amps) BPS-B-3R	400-4000	600 MAX	3PH/4W	Outdoor	Variable	(J) or (L)

## Product Selection (Cabinets)

	Part Number	Transformer Cabinet Size (Inches H x W x D)	Amperage (Amps)	Installation Type	Installation Voltage (Volts AC)
Single Hinged Door	NAV-NG-CTR-8	36 x 36 x 10	400	1-Phase 3-Wire	250
			800	3-Phase 4-Wire	600
Double Hinged Door	NAV-NG-CTR8-FD	36 x 47 x 10	400	1-Phase 3-Wire	250
			800	3-Phase 4-Wire	600

